

PRODUCT NAME

ALPHALITE UV LONG LINER

S&F CODE

ISSUE DATE

24/09/2020

ISSUE NUMBER

001

DESCRIPTION

AlphaLite UV Long Liner is a low-viscosity, highly reactive UV curable resin based on methacrylate esters.

The resin is styrene free.

AlphaLite Long liner has been developed for UV cure pipe rehabilitation process. The resin is suited for both on-site and pre impregnated liners.

MIXING

This resin does not require any mixing

PROPERTIES

Properties	
Mixing Ratio	N/A
Mixed Density	N/A
Power Intensity	At least 10 mW/cm ² with 5cm distance
Equipment	High Pressure mercury lamps or UV-LED's
High Flash Point	>95 degrees
Colour	Yellowish

PACKAGING

All products should be packaged as either a 5kg tub or a 20kg drum.

IDENTIFICATION

ALPHALITE UV Short liner is a one-component system, a transparent light yellowish liquid.


All containers should be clearly labelled with name and weight.

TEST PROTOCOL

Certificate of analysis/conformity to accompany every delivery.

STORAGE

AlphaLite UV Short Liner should be stored indoors in the original, unopened and undamaged packaging in a dry place at temperatures between 5C. and 30C. Store in a dark and 100% light tight containers.

Approval Route	Signature	Date
For Purchaser		
Business Director (Approval)		
	Signature	Date
For Scott & Fyfe Ltd.		13/01/2020

TERMS AND CONDITIONS

For full contractual details please refer to our "Terms & Conditions of Sale" which are available from our Sales Office.

No warranty or guarantee expressed or implied is made regarding the performance of the product since the manner of use and handling is beyond our control.